

## COMET 3 Mixer

5  
YEAR



### Features and Benefits

Hand tightening for easy attachment onto COMET 3 Blowpipe. ('O' ring seals ensure a perfect gas-tight connection every time).

Large flutes on mixer give easy positive handling, even when wearing welding gloves.

Mixer 550 and 570 can be used with either Oxy/Acetylene, Oxy/LP gas or Oxy/Natural gas.

Mixer 574 is an injector mixer design for Oxy/LP gas or Oxy/Natural gas and used for heavy duty high flow applications. For use with SHP3 and SHP4 superheating tips only.

No change required when altering fuel gas, other than the type of tip, hose and regulator required.

Offers high resistance to backfire, regardless of the gas type or flow setting.



Type 550



Type 570



Type 574

Mixer 550 is used for welding and light heating. Mixer 570 and 574 are used for heavy heating applications.

### Spare Parts

**Small O-ring for attach/mixer** Part No: OR28

**Large O-ring for attach/mixer** Part No: 7964006

**O-ring kit** Part No: 304013

NOTE: To protect your product warranty and to ensure a safe, quality repair, use a CIGWELD Accredited Gas Service Repair Provider.

### Specifications

Part No:	Description	Fuel gas type	Welding capacity	Weight
304002	COMET 3 Mixer Type 550	All	up to 25mm	165g
304003	COMET 3 Mixer Type 570	All	–	163g
304166	COMET 3 Mixer Type 574	LP/Nat Gas	–	278g