

X-NA-SV2 Series Datasheet

- Vacuum compatible to 10⁻⁶ Torr
- 25 and 50 mm travel
- Up to 30 mm/s speed and up to 25 N thrust
- Our most compact, precise and robust actuator
- Hardened ball-tip (removable so you can use the built-in threaded tip or a flat tip)
- Built-in controller; daisy chains with other X-series devices inside vacuum chamber
- Designed to replace standard micrometer heads on manual translation stages

X-NA-SV2 Series Overview

For more information about the basics of a vacuum system and considerations to keep in mind when gathering requirements for your application, read our technical article, "Motion Device Design Considerations for Vacuum Applications".

See our Vacuum Compatible TSB-V Linear Slides for more information on compatible slides.

Zaber's X-NA-SV2 Series devices are high-vacuum compatible, computer-controlled, motorized miniature linear actuators with high thrust and speed capabilities, and a compact size. They are stand-alone units requiring only a standard 24 V or 48 V power supply.

These actuators connect to the RS-232 port or USB port of any computer, and they can be daisy-chained with any other Zaber products. The daisy-chain also shares power, making it possible for multiple X-Series products to share a single power supply.

At only 20 mm wide, these miniature actuators are excellent for applications where a small profile is required. The X-NA-SV2 is designed with vacuum compatible materials to minimize outgassing and allow for faster pump down times. Like all of Zaber's products, the X-NA-SV2 Series is designed to be 'plug and play' and very easy to set up and operate.

For more information visit: <https://www.zaber.com/products/vacuum-compatible-stages/X-NA-SV2>

X-NA-SV2 Series Part Numbering

X-NA-SV2 Series Drawings

X-NA-SV2 Series Specifications

Specification	Value	Alternate Unit
Microstep Size (Default Resolution)	0.047625 μm	
Built-in Controller	Yes	
Repeatability	< 1 μm	< 0.000039"
Backlash	< 15 μm	< 0.000591"
Maximum Speed	30 mm/s	1.181"/s
Minimum Speed	0.000029 mm/s	0.000001"/s
Speed Resolution	0.000029 mm/s	0.000001"/s
Encoder Type	None	
Peak Thrust	25 N	5.6 lb
Maximum Continuous Thrust	25 N	5.6 lb
Communication Interface	RS-232	
Communication Protocol	Zaber ASCII (Default), Zaber Binary	
Maximum Current Draw	180 mA	
Power Supply	24-48 VDC	
Power Plug	None, use X-PIB	
Motor Steps Per Rev	200	
Motor Type	Stepper (2 phase)	
Inductance	1.5 mH/phase	
Default Resolution	1/64 of a step	
Data Cable Connection	Teflon flying leads with 4-pin M8 M/F	
Mechanical Drive System	Precision lead screw	
Limit or Home Sensing	Magnetic hall sensor	
Axes of Motion	1	
Mounting Interface	3/8-32 nut, 3/8" shank, or M3 screws	
Operating Temperature Range	0 to 50 $^{\circ}\text{C}$	
Vacuum Compatible	High vacuum (10 ⁻⁶ Torr)	
RoHS Compliant	Yes	
CE Compliant	Yes	

Part Number	Travel Range	Accuracy (unidirectional)	Weight
X-NA08A25-SV2	25.4 mm (1.000")	40 µm (0.001575")	0.156 kg (0.344 lb)
X-NA08A50-SV2	50.8 mm (2.000")	55 µm (0.002165")	0.176 kg (0.388 lb)

Contact

Email: contact@zaber.com

Phone (toll free Canada/USA): 1-888-276-8033

Phone (direct): 1-604-569-3780

Fax: 1-604-648-8033

Zaber Technologies Inc.

#2 - 605 West Kent Ave. N.

Vancouver, British Columbia

Canada, V6P 6T7

<https://www.zaber.com>