

# Photocontrol - Button Thermal Photocontrol, 120 V

## Item K4021C



## **PRODUCT DESCRIPTION**

These photocontrols install within lighting fixtures, post lamps, or in-wall boxes to provide dusk-to-dawn ON/OFF control of outdoor lighting.

#### **FEATURES**

- Mechanical bimetal switch with Cadmium Sulfide photocell
- Compact size fits into standard outlet box, post lamp, wall pack and other lighting fixtures
- Delay feature prevents unwanted OFF switching
- ► 3/8"-18 NPSM, 3/4" long stem with locking nut and washer gasket

# **APPLICATIONS**

Outdoor Lighting Control

## **TECHNICAL DATA**

General	
Model Number	K4021C
Description	Button Thermal Photocontrol, 120 V
UPC Code	078275002005
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited
Usage Environments	Outdoor
Photocontrol Type	Thermal
Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Button
Photocontrol Sensor Location	Front
Control Specifications	
Control Specifications Sensor Time Delay	30 sec to 90 sec
	30 sec to 90 sec Cadmium Sulfide
Sensor Time Delay	
Sensor Time Delay Photocell Type	Cadmium Sulfide
Sensor Time Delay Photocell Type Photo Control Switch Type	Cadmium Sulfide Mechanical Bimetal
Sensor Time Delay Photocell Type Photo Control Switch Type Fail Mode	Cadmium Sulfide Mechanical Bimetal ON
Sensor Time Delay Photocell Type Photo Control Switch Type Fail Mode Activation On	Cadmium Sulfide Mechanical Bimetal ON 1 to 5 fc
Sensor Time Delay Photocell Type Photo Control Switch Type Fail Mode Activation On	Cadmium Sulfide Mechanical Bimetal ON 1 to 5 fc
Sensor Time Delay Photocell Type Photo Control Switch Type Fail Mode Activation On Activation Off	Cadmium Sulfide Mechanical Bimetal ON 1 to 5 fc
Sensor Time Delay Photocell Type Photo Control Switch Type Fail Mode Activation On Activation Off Dimensions	Cadmium Sulfide Mechanical Bimetal ON 1 to 5 fc 3 to 15 fc
Sensor Time Delay Photocell Type Photo Control Switch Type Fail Mode Activation On Activation Off Dimensions Product Height (in)	Cadmium Sulfide Mechanical Bimetal ON 1 to 5 fc 3 to 15 fc 1 13/16
Sensor Time Delay PhotoCell Type Photo Control Switch Type Fail Mode Activation On Activation Off Dimensions Product Height (in) Product Height (mm)	Cadmium Sulfide Mechanical Bimetal ON 1 to 5 fc 3 to 15 fc 1 13/16 46



Product Depth (mm)	20.6
Wire Lead Length (in)	9
Wire Lead Length (mm)	228.6
Wire Size Max	#18 AWG
Material Specifications	
Cover Color	Gray
Housing Material	Polycarbonate
Load Ratings	
Magnetic Ballast Range(s)	8.3 A, 1000 VA
Tungsten Range(s)	15 A, 1800 W
Electrical Specifications	
Wiring Option	Wire leads
Input Voltage Range(s)	120 VAC, 50/60 Hz
Packaging	
Shipping Weight (lbs)	0.25
Unit Carton Dimensions (H x W x D) in	4.88 x 1.75 x 3 in
Environmental Specifications	
Temperature (operation)	-40°C70°C
Standards and Certifications	
UL Certification	UL
CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20
California Proposition 65	DEHP



#### **ACCESSORIES**



6LV1352 Light Shield Accessory for EK4036S, EK4436SM, K4000 Wall Plate Kit for EK4036S, K4000 Series Button Series Button Photocontrols



K43-WP-KIT Photocontrols



LGLBL Lens Sticker Accessory for EK4000 & K4000 Series Photocontrols