

Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 120 V

Item K4251



PRODUCT DESCRIPTION

These photocontrols are provided with a swivel arm for easy and flexible installation to standard outdoor light fixtures or electrical boxes.

FEATURES

- ► Mechanical bimetal switch with Cadmium Sulfide photocell
- ► Delay feature prevents unwanted OFF switching
- ► High strength, UV resistant plastic housing
- ► Swivel with 1/2"-14 NPSM threaded stem
- ► Washer gasket and locking nut included
- ▶ #18 AWG, 6" wire leads

APPLICATIONS

► Outdoor Lighting Control

TECHNICAL DATA

| Company | |
|--------------------------------|---|
| General | |
| Model Number | K4251 |
| Description | Stem and Swivel Mount Thermal Photocontrol, 120 V |
| UPC Code | 078275067752 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CHINA |
| Warranty Period | 1-Year limited |
| Usage Environments | Outdoor |
| Photocontrol Type | Thermal |
| Expected Lifetime (Years) | 5 |
| Expected Lifetime (Operations) | 3650 |
| Application Compatibilities | HID; Fluorescent; Incandescent |
| Photocontrol Style | Stem and Swivel Mount |
| Photocontrol Sensor Location | Тор |

| Control Specifications | |
|---------------------------|--------------------|
| Sensor Time Delay | 30 sec to 90 sec |
| Photocell Type | Cadmium Sulfide |
| Photo Control Switch Type | Mechanical Bimetal |
| Fail Mode | ON |
| Activation On | 1 to 5 fc |
| Activation Off | 3 to 15 fc |

| Dimensions | |
|---------------------|-------|
| Product Height (in) | 4 |
| Product Height (mm) | 101.6 |
| Product Width (in) | 1 3/8 |
| Product Width (mm) | 34.9 |



| Product Depth (in) | 1 3/8 |
|-----------------------|---------|
| Product Depth (mm) | 34.9 |
| Wire Lead Length (in) | 6 |
| Wire Lead Length (mm) | 152 |
| Wire Size Max | #18 AWG |

| Material Specifications | |
|-------------------------|---------------|
| Cover Color | Gray |
| Housing Material | Polycarbonate |

| Load Ratings | |
|---------------------------|----------------|
| Magnetic Ballast Range(s) | 8.3 A, 1000 VA |
| Tungsten Range(s) | 15 A, 1800 W |

| Electrical Specifications | |
|---------------------------|-------------------|
| Wiring Option | Wire leads |
| Input Voltage Range(s) | 120 VAC, 50/60 Hz |

| Packaging | |
|---------------------------------------|--------------------|
| Shipping Weight (lbs) | 0.264 |
| Unit Carton Dimensions (H x W x D) in | 4.88 x 1.75 x 3 in |

| Environmental Specifications | |
|------------------------------|-----------|
| Temperature (operation) | -40°C60°C |
| | |

| Standards and Certifications | |
|--|----------|
| CSA Certification | CSA |
| Other Certifications and Compatibilities | Title 20 |
| California Proposition 65 | DEHP |



ACCESSORIES



22LG116

Light Guard Accessory for K4100 Series, K4200 Series Thermal Photocontrols



K42-SW-A

Swivel Arm Accessory for EK4136S, K4100 Series Stem Light Shield Accessory for EK4036S, EK4436SM, K4000 Mount Photocontrols



6LV1352

Series Button Photocontrols