



# MEA-100B

## AC Resistance Power Supply

High performance welding power supply for precision welding of small parts

- Intuitive user interface for easy operation
- Compact, desktop footprint
- CE certified units available

### KEY FEATURES

- **Secondary constant current control (multi-cycle welding)** – Secondary current feedback every half cycle ensures stable current flow.
- **Single-cycle welding.** First half and second half waves may be programmed separately for small parts welding.
- **Half-cycle welding** – Added precision with half cycle welding capability.
- **Power supply voltage fluctuation compensation control** – Compensates current every half cycle in accordance with fluctuation of power supply voltage.
- **Built-in weld monitor.** Upper and lower limits can be set to monitor the weld quality

	Multi-cycle welding	Single-cycle welding	Half-cycle welding
Secondary constant current control	•	—	—
Power supply voltage fluctuation compensation control	•	•	•

## TECHNICAL SPECIFICATIONS

Model	MEA-100B	
Power requirements	Single phase, 200 / 220 / 230 / 240 / 380 / 400 / 460 / 480 VAC +13% -20%, 50/60 Hz, auto-switch (voltage is selectable but factory-fixed on shipment)	
Maximum output capacity	60 kVA (Duty cycle 1.3% when 200 VAC is input) / 66 kVA (Duty cycle 1.3% when 220 VAC is input) / 68 kVA (Duty cycle 2% when 380 VAC is input) / 72 kVA (Duty cycle 2% when 400 VAC is input) / 86 kVA (Duty cycle 2% when 480 VAC is input)	
Control method	Secondary constant-current control / Power supply voltage fluctuation compensation control	
Welding current supply system	Multi-cycle welding / Single-cycle welding / Half-cycle welding	
Control speed	Half cycle	
Welding current accuracy	Secondary constant-current control	Within +/- 2% against +/- 10% fluctuation of power supply voltage, Within +/- 2% against +/- 10% fluctuation of load
	Power supply voltage fluctuation compensation control	Within +/- 3% against +/- 10% fluctuation of power supply voltage
Timer setting (31 schedules)	Multi-cycle welding	SQUEEZE, WELD1, COOL, WELD2, HOLD: 0 – 99 cycle UPSLOPE1, UPSLOPE2, DOWNSLOPE: 0 – 9 cycle PULSATION: 1 – 9 times
	Single-cycle welding	SQUEEZE, HOLD: 0 – 99 cycle first half and second half wave: 0.5 cycle
	Half-cycle welding	SQUEEZE, HOLD: 0 – 99 cycle, half wave: 0.5 cycle
Current setting (31 schedules)	Secondary constant-current control	Current 1, Current 2: 0.20 – 9.99 kA (0.01 kA incremental)
	Power supply voltage fluctuation compensation control	Current 1, Current 2: 10.0 – 99.9% (0.1% incremental)
Current monitoring (31 schedules)	Secondary constant-current control	Upper limit: +1 to +49%, Lower limit: -1 to -49%
	Power supply voltage fluctuation compensation control	Upper limit: 0.01 – 9.99 kA (0.01 kA incremental) Lower limit: 0.01 – 9.99 kA (0.01 kA incremental)
Optional	MB-400K Toroidal coil (required at secondary constant current control)	
External communication	RS-485, bi-directional communication	
Operating environment	Temperature: 0°–45°C, humidity: 90% or less (no condensation), altitude: 1000 meters or lower	
Power consumption	15 W or less in standby	

## WEIGHT &amp; DIMENSIONS – CONTROLLER

Dimensions (L x W x H)	16.4 in x 5.6 in x 10.6 in (418 mm x 142 mm x 269 mm)
Weight	14.3 lb (6.5 kg)

## WELDING TRANSFORMER SPECIFICATIONS Following transformers can be used when factory supplied power is 200/220 VAC

Model	MT-510AC	MT-520AC	MT-530A *1	MT-25, MT-25A	X16/230	
Rating capacity	1.0 kVA	3.2 kVA	6.0 kVA [4.2 kVA]	11.1 kVA	6.4 kVA	
Primary rated voltage	200 VAC ±10% 50 / 60 Hz				230	
Non-load secondary voltage	1.2 V / 1.8 V / 2.5 V / 3.5 V	2.5 V / 3.2 V / 4.0 V / 5.0 V	2.7 V [2.2 V] / 3.4 V [2.8 V] / 4.3 V [3.6 V] / 5.3 V [4.4 V]	Parallel connection 2.6 V / 4.0 V	Series connection 5.3 V / 8.0 V	1.4 to 5.6 in 9 steps
Transformer turns ratio	167:1 / 111:1 / 80:1 / 57:1	80:1 / 63:1 / 50:1 / 40:1	74:1 / 59:1 / 47:1 / 38:1	77:1 / 50:1	38:1 / 25:1	164:1 to 41:1 in 9 steps
Standard max. input capacity	5.6 kVA	18.5 kVA	35.0 kVA [24.2 kVA]	64.0 kVA		16 kVA
Maximum welding current	1600 A	3700 A	6600 A [5500 A]	8000 A		6500 A
Duty cycle	1.5 % or less				8%	
Cooling	Air cooled			Water cooled (4 liters / min.)		Air cooled
CE	–	–	–	– : MT-25 / X : MT-25A		–
CCC	X	–	X	X		–

## WEIGHT &amp; DIMENSIONS – TRANSFORMERS

Dimensions (L x W x H)*2	11.2 in x 7.6 in x 6.9 in 284 mm x 193 mm x 175 mm	14 in x 7.2 in x 7.75 in 358 mm x 182.5 mm x 197 mm	14.6 in x 9 in x 9.6 in 370 mm x 228 mm x 244 mm	MT-25: 14.5 in x 7 in x 9.5 in 370 mm x 180 mm x 240 mm MT-25A: 18.25 in x 7 in x 8 in 463 mm x 180 mm x 200 mm	14 in x 7.5 in x 13 in 356 mm x 191 mm x 330 mm
Weight	44 lb (20 kg)	77.2 lb (35 kg)	114.6 lb (52 kg)	132.3 lb (60 kg)	95 lb (43 kg)

\*1 Values at 60 Hz input are indicated in brackets [ ]. \*2 Not including projections



## AMADA WELD TECH INC.

1820 S. Myrtle Ave. • Monrovia, CA 91016 US  
T: (626) 303-5676  
info@amadaweldtech.com • www.amadaweldtech.com  
ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

## AMERICAS

**AMADA WELD TECH**  
(Midwest Technical Center)  
Detroit, Michigan  
T: (248) 313-3078  
midwestsales@amadaweldtech.com

**AMADA WELD TECH DO**  
LTDA.  
São Paulo, Brasil  
T: +55-11-4193-3607  
antonio.ruiz@amadaweldtech.com

## EUROPE

**AMADA WELD TECH**  
GmbH  
Munich, Germany  
T: +49-89-839403-0  
infode@amadaweldtech.eu

## ASIA

**AMADA WELD TECH**  
CO., LTD.  
Isehara, Japan  
T: +81-4-7125-6177  
sales@miyachi.com

**AMADA WELD TECH**  
KOREA CO., LTD.  
Seoul, Korea  
T: +82-31-8015-6810  
sales@amadaweldtech.co.kr

**AMADA**  
(THAILAND) CO., LTD.  
Bangkok, Thailand  
T: +66-2170-5900  
info@amada.co.th

**AMADA WELD TECH**  
INDIA PVT., LTD.  
Bangalore, India  
T: +91-80-4092-1749  
info@miyachiindia.com

**AMADA WELD TECH**  
(Mexico Office)  
El Paso, Texas  
T: (915) 881-8765  
mxsales@amadaweldtech.com

**AMADA WELD TECH**  
SHANGHAI CO., LTD.  
Shanghai, China  
T: +86-21-6448-6000  
jwu@msc.miyachi.com

**AMADA WELD TECH**  
TAIWAN CO., LTD.  
Taipei, Taiwan  
T: +886-2-2585-0161

**AMADA**  
VIETNAM CO., LTD.  
Ha Noi, Vietnam  
T: +84-4-6261-4583

follow us on:



Specifications subject to change without notice. Copyright© 2020 AMADA WELD TECH INC. The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.