

4FC FILTER CARTRIDGE

DELIVERS PREMIUM QUALITY WATER FOR FOUNTAIN AND COMBINATION APPLICATIONS

4FC Replacement Cartridge (1 PK): EV9692-21 4FC Replacement Cartridge (6 PK): EV9692-27



APPLICATIONS

Fountain

FEATURES • BENEFITS

- Reduces chlorine taste & odor and other offensive contaminants that can adversely affect the taste of beverages
- Sanitary cartridge replacement is simple, quick and clean; internal filter parts are never exposed to handling or contamination
- Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear
- Improves the taste of fountain beverages and helps retain the drink's carbonation
- Increased capacity for extended reduction of chemical and mechanical contaminants
- Balanced cartridge for optimum performance in varying water qualities

- **INSTALLATION TIPS**
- Install vertically so cartridge hangs down.
- Allow 2½" (6.35 cm) clearance below the cartridge for easy cartridge replacement.
- Flush filter by running water through filter according to cartridge instructions.

OPERATION TIPS

- Replace cartridge when flow rate becomes inconveniently slow or before rated capacity is reached. It is recommended to replace cartridge at least once per year.
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- Always flush the filter cartridge at time of installation and cartridge change.


- Combination Systems
- Compatible with Pentair[§] Everpure[§] Coldrink[§], QC7I, QL2, QL3B, QL3 Heads, and Pentair Everpure High Flow CSR manifolds
- Proprietary Fibredyne[™] II filtration media effectively inhibits the growth of bacteria on the filter media that can decrease product life
- Exclusive Fibredyne II media provides superior chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.2* micron in size by mechanical means
- NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means
 - *Validated by ISO 17025 accredited lab for 99.999% reduction of Pseudomonas diminuta following the ASTM F838-05 protocol for the validation of 0.2 μm sterilizing grade filters.

SIZING

- Service Flow Rate:
 2.5 gpm (9.5 Lpm)
- Rated Capacity: 15,000 gallons (56,781 L)

4FC FILTER CARTRIDGE EV9692-21, EV9692-27

4FC Replacement Cartridge (1 PK): EV9692-21 4FC Replacement Cartridge (6 PK): EV9692-27



SPECIFICATIONS

- Service Flow Rate Maximum 2.5 gpm (9.5 Lpm)
- Rated Capacity 15,000 gallons (56,781 L)
- Pressure Requirements 10 - 125 psi (0.7 - 8.6 bar), non-shock
- Temperature Requirements $35 - 100^{\circ} F (2 - 38^{\circ} C)$
- Overall Dimensions 14.5" H x 3.25" D (36.8 cm x 8.3 cm)



System Tested and Certified by NSF International against NSF/ ANSI Standards 42 and 53 for the reduction of:



Chlorine Mechanical Filtration Nominal Particulate Class

STANDARD NO. 42 -STANDARD NO. 53 -AESTHETIC EFFECTS Bacteriostatic Effects Chemical Reduction Taste & Odor

HEALTH EFFECTS Mechanical Filtration Cyst Turbidity

EPA Est. No. 002623-IL-002

WARRANTY

Everpure water treatment systems by Pentair (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.

> India Boulevard, B-9/A, 7th Floor - Tower B Sector 62 Noida - 201301 91.120.419.9444 Tel indiacustomer@pentair.com

PENTAIR

World Headquarters 1040 Muirfield Drive Hanover Park, IL 60133 **United States** 800.942.1153 (US Only) 630.307.3000 Main cseverpure@pentair.com

Europe Pentair Water Belgium BVBA Industriepark Wolfstee, Toekomstlaan 30, **B-2200 Herentals** Belgium +32.(0).14.283.504 Tel sales@everpure-europe.com Australia 1-21 Monash Drive Dandenong South, Vic 3175 Australia 011.1300.576.190 Tel au.everpure@pentair.com

Japan Inc. Hashimoto MN Bldg. 7F, 3-25-1 Hashimoto, Midori-ku, Sagamihara-shi Kanagawa 252-0143 Japan 81.(0)42.775.3011 Tel info@everpure.co.jp

China 21F Cloud 9 Plaza, NO 1118 Shanghai, 200052 China 86.21.3211.4588 Tel china.water@pentair.com

Southeast Asia 390 Havelock Road, #04-01 King's Centre Singapore 169662 65.6768.5800 Tel cseverpure@pentair.com

§ Pentair trademarks and logos are owned by Pentair plc or its affiliates. For a detailed list of where Pentair trademarks are registered, please visit www.pentair.com/en/registrations.html. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

EV9692-21-27 MR20 ©2019 Pentair Filtration Solutions, LLC. All Rights Reserved.