PHOTONIS
Digital Vision

iNOCTURN

ULTRA SENSITIVE **INTENSIFIED** CAMERA

Detect at each wavelength from UV through NIR

NOCTURN

Applications

- Fluorescence imaging
- Subsea imaging
- Active imaging
- Electrical discharge detection
- Radioactive source detection
- Wafer inspection
- Spectroscopy
- Microscopy
- Industrial imaging

HI-QE Photocathodes



Specifications

Camera resolution	1280x1024 pixels
Frame rate	Up to 100 fps at full resolution
Spectral range	200 - 1100 nm subject to photocathode choice
Gating options	Non-gated, Auto-gated, Fast-gated (up to 3 ns)
Minimum detection capability	Up to single photon
Connection	PAL/NTSC, CameraLink, HD-SDI, USB 3.0, LVCMOS
Lens mount	C-mount
Operational temperature	-10°C to +55°C

Contact Us

digitalvision@photonis.com
www.photonis.com
@PhotonisScience
fb.com/photonis
Photonis

The Information provided in this document is believed to be accurate and reliable but it is not guaranteed as such and is subject to change without notice. No liability is assumed for its use. Performance data represents typical characteristics as individual product performance may vary. Customers should ensure that they have up-to-date Photonis product information before placing orders. Text and pictures are not contractually binding. Photonis makes no representations or warranties as to the application of Photonis products. This document may not be reproduced, in whole or in part without the prior written consent of Photonis.