

3/4" BSPP Automatic Tap Timer with Digital Display



Features

- UV resistant material, long term outdoor use, the product won't be deformed, aging, cracking.
- Waterproof level IP55
- Dual mode smart watering, Wider range of run time and interval, can apply to drip irrigation systems, rain buckets, pet water and sprinkler irrigation etc.
- Watering Duration: 1min-23H59min
- Watering Frequency: 1min-23H59min,1-7days
- Child Lock mode, effectively avoid unintended trigger by kids& pets and prevent water waste.
- Manual rain delay is available in our water faucet timer to prevent over-watering and save much water in rain days, 1-7days.
- Manual mode allows instant watering use without interrupting your set irrigation program.
- 40 x 25mm large screen
- Battery over 6 months working time.
- You can simply set the current time, start time, watering duration, watering frequency, rain delay and manual watering according to your needs on the large dial buttons



Technical Data

| | | | |
|---------------------------------|--|----------------------------|---|
| Port size | 3/4" BSPP | Medium | Water |
| Maximum Working Pressure | 0.8 MPa (8 bar) | Screen Size | 40 x 25 mm |
| Minimum Working Pressure | 0.05 MPa (0.5 bar) | Manual Override | Yes |
| Working voltage | DC 3.5V | IP Rating | IP55 |
| Battery | 2 x AA Alkaline Battery (not included) | Dual Mode | How Long: 1 min - 23H 59 min How Often: 1 min - 23H 59 min, 1 ~ 7 days |
| Low Battery Protection | Yes, Lower 2.8V | Standby Time | More than 6 months |
| Rain Delay | Yes, 1 ~ 7 days | Other Function | Child Lock, Valve Close while the batteries are installed |
| Setting Method | Knob & Button | Working temperature | 4.5°C ~ 45°C |
| Button | Silicon | Surface | Frosting |
| Colour | Grey & Black | Dimensions | 10.7cm x 6.3cm x 4.1cm |

Packaging Includes:

- 1 x Tap Timer
- User Manual
- 1/2" BSPP Female to 3/4" Male Adapter
- 3/4" BSPP to 1/2" Barbed Fitting (Hose Connection Fitting)
- Teflon Tape

