

▼ Shown: HC-7206



Thermo-Plastic Safety Hoses (700-Series)

- For demanding applications, featuring a 4:1 safety factor
- Maximum working pressure of 700 bar
- Outside jacket is polyurethane, to provide maximum abrasion resistance
- Exhibits low volumetric expansion under pressure to enhance overall system efficiency
- Crimped-on rubber strain relief for improved life and durability on all models.

▼ To prevent back pressure and to increase cylinder retraction speed, when using long hoses with single-acting cylinders, the Enerpac HC-7300-Series of hoses with increased internal diameter is the best choice.



Safety and Quality



To ensure the integrity of your system, specify only Enerpac hydraulic hoses.

WARNING !

- Do not exceed 700 bar maximum pressure.
- Do not handle hoses which are under pressure.

More safety instructions in our 'Yellow pages'.

Page: **246**

▼ Hose End Couplings

1/4" NPTF	
3/8" NPTF	
A-604	
A-630	
AH-604	
AH-630	
C-604	
CH-604	

High Pressure Hydraulic Hoses

H700 Series



Inside Diameter:


6,4 - 9,7 mm

Length:

0,6 - 15 m

Maximum Operating Pressure:

700 bar

Internal Diameter (mm)	Hose End Assemblies and Couplers *		Hose Length (m)	Model Number	 (kg)	
	End one	End two				
6,4	1/4" NPTF		-	-	-	
			-	-	-	
		A-630	1,8	HB-7206QB	1,1	
			-	-	-	
		CH-604	1,8	HC-7206Q	1,0	
	3/8" NPTF			0,6	H-7202	0,5
				0,9	H-7203	0,7
				1,8	H-7206	0,9
				3,0	H-7210	1,4
				6,1	H-7220	2,8
				9,1	H-7230	4,5
				15	H-7250	7,0
				-	-	-
		A-604	1,8	HA-7206B	1,1	
			-	-	-	
		AH-604		-	-	-
				1,8	HA-7206	1,0
				3,0	HA-7210	1,5
				-	-	-
		AH-630	1,8	HB-7206	1,0	
		C-604		0,9	HC-7203B	1,0
			1,8	HC-7206B	1,3	
			3,0	HC-7210B	1,8	
	CH-604		0,9	HC-7203	0,8	
		1,8	HC-7206	1,0		
		3,0	HC-7210	1,5		
		6,1	HC-7220	2,9		
CH-604	CH-604		1,8	HC-7206C	1,1	
			15	HC-7250C	7,0	
9,7	3/8" NPTF		1,8	H-7306	1,6	
				-	-	-
				3,0	H-7310	2,4
				6,1	H-7320	4,5
				9,1	H-7330	7,3
		CH-604		15	H-7350	11,5
				1,8	HC-7306	1,7
				3,0	HC-7310	2,5
				6,1	HC-7320	5,1
				-	-	-

* For technical information on couplers see next page.



Torque Wrench Hoses

Use Enerpac twin safety hoses with double-acting wrenches to ensure the integrity of your hydraulic system.

Page: **200**



Fittings

For additional fittings see the fitting page of the System Components section.

Page: **121**

Hose Oil Capacity

When using greater hose lengths, it is sometimes necessary to fill the pump reservoir after filling the hoses. To determine the hose oil capacity, use the following:

For 6,4 mm inside diameter hoses:
Capacity (cm³) = 32,1699 x Length (m)

For 9,7 mm inside diameter hoses:
Capacity (cm³) = 73,8981 x Length (m)