



## EL5151, EL5152 | 1-, 2-channel incremental encoder interface

The EL5151/EL5152 EtherCAT Terminal is an interface with 24 V inputs for the direct connection of incremental encoders. With the EL5151, a 32 bit counter with a quadrature decoder and a 32 bit latch for the zero pulse can be read, set or enabled. Alternatively, the EL5151 can be used as up/down counter terminal with gate.

With the EL5152, two 32 bit counters with quadrature decoder can be read and set. The EL515x supports the synchronous reading of the encoder value, together with other input data, into the EtherCAT system via high-precision EtherCAT distributed clocks (DC).

Technical data	EL5151   ES5151	EL5152   ES5152
<b>Technology</b>	incremental encoder interface 24 V DC, EN 61131-2, type 1, "0": < 5 V DC, "1": > 15 V DC, typ. 5 mA	
<b>Number of channels</b>	1	2
<b>Encoder connection</b>	A, B, C, gate/latch input 24 V DC, 24 V/0 V	A1, B1, A2, B2, 24 V/0 V
<b>Sensor inputs</b>	1	2
<b>Encoder operating voltage</b>	24 V DC	
<b>Counter</b>	1 x 16/32 bit switchable	2 x 32 bit
<b>Limit frequency</b>	400,000 increments/s (with 4-fold evaluation)	
<b>Quadrature decoder</b>	4-fold evaluation	
<b>Commands</b>	read, set, latching	
<b>Distributed clocks</b>	yes	
<b>Input signal</b>	24 V DC	
<b>Supply voltage</b>	24 V DC (-15 %/+20 %)	
<b>Nominal voltage</b>	24 V DC at power contact	
<b>Current consumption power contacts</b>	typ. 100 mA + load	
<b>Input frequency</b>	max. 400,000 increments/s (with 4-fold evaluation)	
<b>Resolution</b>	1/256 bit microincrements	
<b>Current consumption E-bus</b>	typ. 130 mA	
<b>Bit width in the process image</b>	14 byte ENC input, 6 byte ENC output	28 byte ENC input, 12 byte ENC output
<b>Special features</b>	gate or latch function, microincrements, time stamping of edges, period duration and frequency measurement, up/down counters	microincrements, period duration and frequency measurement, up/down counters
<b>Weight</b>	approx. 50 g	
<b>Operating/storage temperature</b>	-25...+60 °C/-40...+85 °C	
<b>Relative humidity</b>	95 %, no condensation	
<b>Vibration/shock resistance</b>	conforms to EN 60068-2-6/EN 60068-2-27	
<b>EMC immunity/emission</b>	conforms to EN 61000-6-2/EN 61000-6-4	
<b>Protect. class/installation pos.</b>	IP 20/variable	
<b>Pluggable wiring</b>	for all ESxxxx terminals	
<b>Approvals</b>	CE, UL, Ex	

**Special terminals****EL5151-0021**

1-channel incremental encoder interface with parameterisable 24 V DC output

**Product announcement****EL5151, ES5151, EL5152, ES5152: available**

EL5151-0021: estimated market release 1st quarter 2016