

OUTPUT INTERFACE 1 CO, SCREW CONNECTION AC/DC 24 V,
HOUSING WIDTH 6.2 M



Figure similar

General technical data:

Type of voltage	AC/DC
Supply voltage frequency for auxiliary and control current circuit rated value	50 ... 60 Hz
Control supply voltage	
• at AC	
— at 50 Hz rated value	
— minimum	24 V
— maximum	24 V
— at 60 Hz rated value	
— minimum	24 V
— maximum	24 V
• at DC rated value	
— minimum	24 V
— maximum	24 V
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts for auxiliary contacts	1
Operating current of auxiliary contacts	

<ul style="list-style-type: none"> • at DC-13 <ul style="list-style-type: none"> — at 24 V — at 110 V — at 230 V • at AC-15 <ul style="list-style-type: none"> — at 230 V 	1 A 0.2 A 0.1 A 3 A
Switching behavior	monostable
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K


Mechanical data:

Type of electrical connection	screw-type terminals
Type of electrical connection Plug-in socket	No
Design of the relay operating mechanism	poled
Design of the switching function positively driven	No
Product component Plug-in socket	No
Width	6.2 mm
Height	78 mm
Depth	87 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +60 °C

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	other
 CCC	 UL		 EG-Konf.

other

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>